



SAFETY DATA SHEET AD 75W-90 GEAR OIL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name AD 75W-90 GEAR OIL

Product number AID001, AID005, AID020

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Gear oil.

1.3. Details of the supplier of the safety data sheet

Supplier TETROSYL LIMITED
Bury
Lancashire
England
BL9 7NY
0161 764 5981
0161 797 5899
info@tetrosyl.com

Manufacturer TETROSYL LIMITED
Bury
Lancashire
England
BL9 7NY
0161 764 5981
0161 797 5899
info@tetrosyl.com

1.4. Emergency telephone number

Emergency telephone +44 (0)161 764 5981

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Hazard pictograms



AD 75W-90 GEAR OIL

| | |
|---------------------------------|---|
| Hazard statements | <p>EUH208 Contains REACTION PRODUCTS OF BIS(4-METHYLPENTAN-2-YL)DITHIOPHOSPHORIC ACID WITH PHOSPHORUS OXIDE, PROPYLENE OXIDE AND AMINES, C12-14 ALKYL (BRANCHED), REACTION PRODUCTS OF 1,3,4-THIADIAZOLIDINE-2,5-DITHIONE, FORMALDEHYDE AND PHENOL, HEPTYL DERIVS."..</p> <p>May produce an allergic reaction.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p> |
| Precautionary statements | <p>P101 If medical advice is needed, have product container or label at hand.</p> <p>P102 Keep out of reach of children.</p> <p>P273 Avoid release to the environment.</p> <p>P391 Collect spillage.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p> |

2.3. Other hazards

Not applicable.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| | |
|--|-------------------|
| DISTILLATES (PETROLEUM) <3% DMSO EXTRACT (IP 346) | 60-100% |
| CAS number: 64742-55-8 EC number: 265-158-7 REACH registration number: 01-2119487077-29-0000 | |
| Classification Asp. Tox. 1 - H304 | |
| DISTILLATES, HYDROTREATED HEAVY PARAFFINIC <3% DMSO EXTRACT (IP 346) | 10-<30% |
| CAS number: 64742-54-7 EC number: 265-157-1 REACH registration number: 01-2119484627-25-0000 | |
| Classification Asp. Tox. 1 - H304 | |
| REACTION PRODUCTS OF BIS(4-METHYLPENTAN-2-YL)DITHIOPHOSPHORIC ACID WITH PHOSPHORUS OXIDE, PROPYLENE OXIDE AND AMINES, C12-14 ALKYL (BRANCHED) | 0.5-<1% |
| CAS number: — EC number: 931-384-6 REACH registration number: 01-2119493620-38-0000 | |
| Classification Acute Tox. 4 - H302 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411 | |

AD 75W-90 GEAR OIL

| | |
|---|--|
| OLEYLAMINE | 0.5-<1% |
| CAS number: 112-90-3 | EC number: 204-015-5 |
| M factor (Acute) = 10 | M factor (Chronic) = 10 |
| Classification Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 STOT SE 3 - H335 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410 | |
| REACTION PRODUCTS OF 1,3,4-THIADIAZOLIDINE-2,5-DITHIONE, FORMALDEHYDE AND PHENOL, HEPTYL DERIVS." | 0.1-<0.3% |
| CAS number: — | EC number: 939-460-0 |
| | REACH registration number: 01-2119971727-23-0000 |
| Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412 | |
| BUTYLATED HYDROXYTOLUENE | <0.1 |
| CAS number: 128-37-0 | EC number: 204-881-4 |
| | REACH registration number: 01-2119565113-46-0000 |
| M factor (Acute) = 1 | M factor (Chronic) = 1 |
| Classification Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410 | |

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|----------------------------|--|
| General information | Get medical attention if any discomfort continues. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Effects may be delayed. Keep affected person under observation. Remove affected person from source of contamination. |
| Inhalation | If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. |
| Ingestion | Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if a large quantity has been ingested. Show this Safety Data Sheet to the medical personnel. |
| Skin contact | Remove contaminated clothing immediately and wash skin with soap and water. Rinse with water. Get medical attention if any discomfort continues. |

AD 75W-90 GEAR OIL

Eye contact Get medical attention promptly if symptoms occur after washing. Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Do not rub eye.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Effects may be delayed. Keep affected person under observation.

Inhalation May cause an asthma-like shortness of breath. Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion May cause discomfort if swallowed. May cause stomach pain or vomiting.

Skin contact Skin irritation. Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. Blistering may occur.

Eye contact Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain. May cause blurred vision and serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Foam, carbon dioxide or dry powder. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards No unusual fire or explosion hazards noted.

Hazardous combustion products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting No specific firefighting precautions known.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces. Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Collect and dispose of spillage as indicated in Section 13.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

AD 75W-90 GEAR OIL

7.1. Precautions for safe handling

Usage precautions Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Avoid contact with skin and eyes. Do not handle broken packages without protective equipment. Do not eat, drink or smoke when using the product. Provide adequate ventilation. Avoid the formation of mists.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep containers upright. Store in tightly-closed, original container.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

No exposure limits known for ingredient(s).

BUTYLATED HYDROXYTOLUENE

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³

WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

Other skin and body protection

Wear suitable protective clothing as protection against splashing or contamination.

Hygiene measures

When using do not eat, drink or smoke. Wash hands after contact. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash contaminated clothing before reuse. Promptly remove any clothing that becomes contaminated.

Respiratory protection

No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Clear liquid.

Colour Brown.

AD 75W-90 GEAR OIL

| | |
|---|-------------------------------|
| Odour | Oil-like. |
| Melting point | Not determined. |
| Initial boiling point and range | >250°C @ 1.013 hPa |
| Flash point | 220°C |
| Evaporation rate | Not determined. |
| Upper/lower flammability or explosive limits | Not determined. |
| Vapour pressure | Not determined. |
| Vapour density | Not determined. |
| Relative density | 0.857g/cm ³ @ 20°C |
| Solubility(ies) | Insoluble in water. |
| Partition coefficient | Not determined. |
| Auto-ignition temperature | Not determined. |
| Decomposition Temperature | Not determined. |
| Viscosity | 90 mm ² /s @ 40°C |

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability No particular stability concerns.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not applicable.

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid Alkali metals. No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.

AD 75W-90 GEAR OIL

| | |
|---|---|
| Inhalation | No specific health hazards known. |
| Ingestion | May cause discomfort if swallowed. |
| Skin contact | Prolonged and frequent contact may cause redness and irritation. May cause an allergic skin reaction. |
| Eye contact | May cause temporary eye irritation. |
| Acute and chronic health hazards | This product may cause skin and eye irritation. |

SECTION 12: Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish Not available.

Acute toxicity - aquatic invertebrates Not available.

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

12.4. Mobility in soil

Mobility The product is insoluble in water.

Adsorption/desorption coefficient Not available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not applicable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Confirm disposal procedures with environmental engineer and local regulations.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

AD 75W-90 GEAR OIL

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Issued by Health & Safety Department

Revision date 15/01/2020

Revision 2

Supersedes date 16/12/2019

SDS number 33557

SDS status Approved.

AD 75W-90 GEAR OIL

Hazard statements in full

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH208 Contains REACTION PRODUCTS OF BIS(4-METHYLPENTAN-2-YL)DITHIOPHOSPHORIC ACID WITH PHOSPHORUS OXIDE, PROPYLENE OXIDE AND AMINES, C12-14 ALKYL (BRANCHED), REACTION PRODUCTS OF 1,3,4-THIADIAZOLIDINE-2,5-DITHIONE, FORMALDEHYDE AND PHENOL, HEPTYL DERIVS.".. May produce an allergic reaction.