TECHNICAL DATA SHEET

AD 5W-30

A5/B5 Semi Synthetic
AD-Tec 44

Properties

Property	Result
SAE Viscosity Grade	5W-30
Density @ 15°C (g/ml)	0.860
Kinematic Viscosity (mm/s)	@ 40°C 73.50
	@100°C 11.70
Viscosity Index (VI)	154
Pour Point (°C)	-39
Flash Point (°C)	220
Sulphated Ash (%)	1.25
TBN (mgKOH/g)	8.892

Product Reference

Size	Part No	Barcode
5 Litre	AAG005	5010373119921
20 Litre	AAG020	5010373119938
199 Litre	AAG199	5010373119945

AD 5W-30 Semi Synthetic AD-Tec 44 Performance Specifications

Issuing Body	Performance Specification
ACEA	A5/B5
API	SL/CF

Environmental Protection & Safety Precautions

Do not pour used surplus oil down sewers or drains. Dispose of used or surplus oil at your nearest oil-recycling bank. Dispose of empty packs in a responsible manner. Store container in an upright position and secure when transported. Wear goggles if splashing risk. Avoid exposure to oil mist. When using oil do not eat, drink or smoke. Wash hands after use.

Disclaimer

This Product Information Sheet does not constitute to any extent a fitness for purpose warranty or a quality specification. It is intended to be indicative only of the general characteristics of the product(s) and may not be relied upon (in whole or in part) in substitution of nor as a supplement to any of the information and/or instructions and/or warnings set out on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet (which is available on request).
Users of a product marked "For Professional Use Only" are deemed to declare and acknowledge for themselves professional levels of skill, knowledge, competence and experience in the selection and use of such product(s).
Product Information Sheets are updated from time to time and inquiries should be made on a regular basis to ensure that this is the latest version available.